





Product Code	Description
GC8513SUSBC	13A 1 Gang Switched BS Socket Outlet with 2 Port USB A + C Charger (2.1A Max)



GC8513SUSBC-BFSS

Technical Specification

- Socket rated voltage:
250VAC, 50/60Hz
- Socket rated current: 13A
- USB Charger input supply:
250V 50/60Hz, 0.5A max.
- USB Charger output:
5VDC/2.1A max.
(USB-A + USB-C Shared)
- USB Charger with built-in over-heat, overload and short-circuit protection
- Recommended wire size:
2.5mm² - 4mm²
- Dimensions: 86x86x4 (WxHxD)
- Fix Center: 60.3mm
- Fix Screws (2x each):
M3.5x0.6x25mm±
M3.5x0.6x30mm±
- Mounting box: > 35mm
 - R1150, flush mounting, plastic (80x80x48.4 mm) (WxHxD)
 - M1247, flush mounting, metal (79x73x47 mm) (WxHxD)
- Comply to standards:
IEC 62368-1/ IEC 60950-1
BS1363

Product Code	Colour
GC8513SUSBC-BFSS	 Black Interior, Stainless Steel, Fingerprint Proof, Statin Nickel
GC8513SUSBC -BFMR	 Black Interior, Electroplated with Matt Brass, Fingerprint Proof, Satin Brass
GC8513SUSBC -BSBL	 Black Interior, Matt Black
GC8513SUSBC -BLQB	 Black Interior, Antique Brass
<i>For other colours, please contact T&J Sales representative</i>	