

Specifications

Electrical:

Socket

- Rated Voltage: 250VAC 50/60Hz
- Rated Current: 16A
- Recommended wire size: 2.5mm²- 4mm²

USB Charger

- Input Voltage: 100-240VAC 50/60Hz
- Input Current: 0.2A max.
- Output Wattage: 20W max.
- Output Voltage: 5-20VDC*

*Refer to Charger Output Voltage Table

Mechanical:

- Overall dimension: 88mm x 86mm x 32mm (HxWxD)
- Fixing screws centre: 60.3mm
- BS 4662 wall box compatible

Standards:

- IEC-60884-1
- IEC-62368-1



USB Charger Output Voltage Table:

Single port in use: A or C (20W max)		Two ports in use: A and C (20W max)	
USB-A (QC 2/3)	USB-C (PD)	USB-A	USB-C
5V, 3.1A	5V, 3.1A	5V, 2A	5V, 2A
9V, 2.1A	9V, 2.1A		
12V, 1.5A	12V, 1.5A		
20V, 1.0A	20V, 1.0A		

Ordering information

Colour	Part No.
White	GA8318SUSBC-WH
Champagne Grey	GA8318SUSBC-ST5
Champagne	GA8318SUSBC-PS7
Matt Black	GA8318SUSBC-SBL

The information given in this document may be amended. You are also reminded that all products must be installed by a qualified professional.